



GROUND LEVEL

TETHER POINT

ALUMINUM PIPE ANCHOR  
2" x 3" O.D.

FOOTING: AMOUNT OF CONCRETE WILL  
DEPEND ON SOIL CONDITIONS; GENERAL  
RECOMMENDATION IS 12" WIDTH X 18" DEPTH.  
TOP PIPE SHOULD BE FLUSH WITH GROUND  
LEVEL.

WRAP CABLE THROUGH  
AS SHOWN

6" X 1/2" ALUMINUM ROUND  
PREVENTS ANCHOR FROM PULLING UP

NOTE:  
MINIMUM ONE (1) PERMANENT ANCHOR PER GOAL.  
POSITION ANCHOR WITH CENTER OF REAR CROSSBAR.  
WRAP CABLE PROVIDED WITH GOAL AROUND REAR CROSSBAR  
AND DOWN TO TETHER POINT AND SECURE WITH PADLOCK.  
PADLOCK NOT INCLUDED.

18"

2"

( 2" )



Part Name:		SM-GT1000	
Size:	Date:	Wednesday, April 09, 2008 3:37:43 PM	
A		Scale: 1:3	Drawn By:
			Sheet 1 of 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SCOREMASTER  
ANY REPRODUCTION IN PART OR IN WHOLE WITHOUT THE WRITTEN PERMISSION OF SCOREMASTER IS PROHIBITED

File Path: W:\Projects by Customer\Scoremaster\SolidWorks Files\